

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): An information recording apparatus in which in an information recording apparatus for recording main data by forming a pit row or a mark row to an information recording medium by irradiating the information recording medium with a beam for recording, said information recording apparatus comprising:

first modulating signal generating means for generating a first modulating signal in correspondence with the pit row or the mark row;

second modulating means for generating a second modulating signal by modulating the first modulating signal by sub-data such that a pit or a mark of the pit row or the mark row is locally changed in accordance with a logical level of the sub-data; and

beam modulating means for modulating the beam for recording by the second modulating signal;

wherein the second modulating means generates the second modulating signal by allocating one bit of the sub-data to the pit row or the mark row, the pit row or the mark row having a predetermined minimum length to which one bit of the sub-data is allocated that is ~~long enough such that a local change to the pit row or mark row will not affect the main data from being correctly reproduced such that the sub-data can correctly be reproduced~~ a length by which the sub-data is correctly reproduced in a case in which the main data is correctly reproduced by an error correction code and a length by which the area to which one bit of the sub-data is allocated can be detected by optical observation.

Claim 2 (Currently Amended): The information recording apparatus according to Claim 1, wherein the predetermined minimum length is a length of 1 ~~{mm}~~ mm or more.

Claim 3 (Canceled).

Claim 4 (Previously Presented): The information recording apparatus according to

Claim 1, wherein the second modulating means comprises:

binary coefficient row generating means for generating a binary coefficient row with the first modulating signal as a reference;

disturbing means for generating a disturbing signal by disturbing the sub-data by the binary coefficient row; and

signal modulating means for generating the second modulating signal by modulating the first modulating signal by the disturbing signal.

Claim 5 (Original): The information recording apparatus according to Claim 4, wherein the binary coefficient row is a binary coefficient row of M series.

Claim 6 (Original): The information recording apparatus according to Claim 4, wherein the binary coefficient row generating means generates at least a first and a second one of the binary coefficient rows, the disturbing means generates a first and a second one of the disturbing signals by disturbing a first and a second one of the bit rows by the sub-data respectively by the first and the second binary coefficient rows and generates the disturbing signal by multiplexing the first and the second ones of disturbing signals.

Claim 7 (Original): The information recording apparatus according to Claim 6, wherein the disturbing signal is generated by multiplexing the first and the second ones of the disturbing signals by selecting the first and the second ones of the disturbing signals in accordance with a predetermined random number.

Claim 8 (Original): The information recording apparatus according to Claim 4, wherein the binary coefficient row generating means initializes the binary coefficient row at a constant period with the first modulating signal as a reference.

Claim 9 (Original): The information recording apparatus according to Claim 1, wherein the first modulating means generates the first modulating signal by ciphering whether the main data and the sub-data is data necessary for deciphering the main data.

Claim 10 (Currently Amended): An information recording method, wherein in an information recording method for recording main data by forming a pit row or a mark row on an information recording medium by irradiating the information recording medium with a beam for recording, said information recording method comprising:

a step of generating a second modulating signal by modulating a first modulating signal in correspondence with a pit row or a mark row by sub-data in accordance with a logical level of the sub-data such that a pit or a mark of the pit row or the mark row is locally changed; and

a step of modulating the beam for recording by the second modulating signal and irradiating the information recording medium with the modulated beam for recording,

wherein the second modulating signal is generated by allocating one bit of the sub-data to the pit row or the mark row, the pit row or the mark row having a minimum predetermined length to which one bit of the sub-data is allocated that is ~~long enough such that a local change to the pit row or mark row will not affect the main data from being reproduced correctly such that the sub-data will be reproduced correctly~~ a length by which the sub-data is correctly reproduced in a case in which the main data is correctly reproduced

by an error correction code and a length by which the area to which one bit of the sub-data is allocated can be detected by optical observation.

Claim 11 (Previously Presented): An information recording medium, recorded with main data by a pit row or a mark row, recorded by a process comprising recording sub-data by a local change of a pit or a mark of the pit row or the mark row and one bit of the sub-data is allocated to the bit row or the mark row, the pit row or the mark row having a predetermined minimum length to which one bit of the sub-data is allocated that is long enough such that a local change to the pit row or mark row will not affect the main data from being reproduced correctly such that the sub-data will be correctly reproduced.

Claim 12 (Currently Amended): The information recording medium according to Claim 11, wherein the predetermined minimum length is a length of 1 ~~{mm}~~ mm or more.

Claim 13 (Canceled).

Claim 14 (Original): The information recording medium according to Claim 11, wherein the local change is formed in accordance with a disturbing signal disturbing the sub-data by a binary coefficient row.

Claim 15 (Original): The information recording medium according to Claim 14, wherein the binary coefficient row is a binary coefficient row of M series.

Claim 16 (Original): The information recording medium according to Claim 14, wherein the binary coefficient row comprises at least a first and a second one of the binary

coefficient rows and the disturbing signal is generated by multiplexing a first and a second one of the disturbing signals generated by disturbing a first and a second one of the pit rows by the sub-data by the first and the second ones of binary coefficient rows.

Claim 17 (Original): The information recording medium according to Claim 16, wherein the first and the second ones of disturbing signals are selected in accordance with a predetermined random number to thereby generate the disturbing signal.

Claim 18 (Original): The information recording medium according to Claim 14, wherein the binary coefficient row is initialized at a constant period with the pit row or the mark row as a reference.

Claim 19 (Original): The information recording medium according to Claim 11, wherein the main data is ciphered and recorded and the sub-data is data necessary for deciphering the main data.

Claim 20 (Currently Amended): An information reproducing apparatus, wherein in an information reproducing apparatus for irradiating an information recording medium recorded with main data by a pit row or a mark row with a laser beam and receiving a return beam to thereby reproduce the main data, said information reproducing apparatus comprising:  
reproduced signal generating means for receiving the return beam and generating a reproduced signal, a signal level of which is changed in accordance with the pit row or the mark row;

main decoding means for decoding the main data from the reproduced signal;

sampling means for sampling the reproduced signal and outputting a sampling signal;  
and

sub decoding means for reproducing sub-data recorded by a local change in a pit or a mark of the pit row or the mark row by repeating to integrate the sampling signal for a predetermined time period;

wherein the sub decoding means is set with an integrating time period in correspondence with one bit of the sub-data as a time period by which the pit row or the mark row have a minimum size to which one bit of the sub-data is allocated that is ~~long enough~~ such that a local change to the pit row or mark row will not affect the main data from being correctly reproduced, and the sub-data will also be decoded correctly a length by which the sub-data is correctly reproduced in a case in which the main data is correctly reproduced by an error correction code and a length by which the area to which one bit of the sub-data is allocated can be detected by optical observation.

Claim 21 (Currently Amended): The information reproducing apparatus according to Claim 20, wherein the integrating time period in correspondence with the one bit of the sub-data is a time period in correspondence with a length of 1 ~~{mm}~~ mm or more of the pit row or the mark row.

Claim 22 (Canceled).

Claim 23 (Original): The information reproducing apparatus according to Claim 20, further comprising:

binary coefficient row generating means for generating a binary coefficient row with the reproduced signal as a reference;

wherein the sub decoding means integrates the sampling signal in accordance with the binary coefficient row.

Claim 24 (Original): The information recording apparatus according to Claim 23, wherein the binary coefficient row is a binary coefficient row of M series.

Claim 25 (Original): The information reproducing apparatus according to Claim 23, wherein the binary coefficient row generating means generates at least a first and a second one of the binary coefficient rows and the sub decoding means decodes the sub-data by a first and a second one of the bit rows in correspondence with the first and the second ones of the binary coefficient rows by integrating the sampling signal respectively in accordance with the first and the second ones of the binary coefficient rows.

Claim 26 (Original): The information recording apparatus according to Claim 23, wherein the binary coefficient row generating means initializes the binary coefficient row at a constant period with the reproduced signal as a reference.

Claim 27 (Original): The information reproducing apparatus according to Claim 20, wherein the main decoding means deciphers the main data based on the sub-data.

Claim 28 (Currently Amended): An information reproducing method, wherein in an information reproducing method for irradiating an information recording medium recorded with main data by a pit row or a mark row with a laser beam and receiving a return beam to thereby reproduce the main data, said information reproducing method comprising:

a step of decoding the main data from a reproduced signal, a signal level of which is changed in accordance with the pit row or the mark row provided by receiving the return beam; and

a step of reproducing sub-data recorded by a local change in a pit or a mark of the pit row or the mark row by repeating to integrate a sampling signal provided by sampling the reproduced signal for a predetermined time period;

wherein an integrating time period in correspondence with one bit of the sub-data is set to a time period by which the pit row or the mark row have a minimum size to which one bit of the sub-data is allocated that is ~~long enough such that a local change to the pit row or mark row will not affect the main data from being reproduced correctly, and the sub-data will also correctly be reproduced~~ a length by which the sub-data is correctly reproduced in a case in which the main data is correctly reproduced by an error correction code and a length by which the area to which one bit of the sub-data is allocated can be detected by optical observation.